





## Pacific LED Waterproof Batten

Pacific LED Waterproof batten is a high performance luminaire, replacing traditional fluorescent fittings. With comparable lumen outputs, Pacific LED will save up to 50% energy, and lasts 50,000 hours. Further savings can be achieved through DALI dimming, and comes in a variety of lengths and beam angles. There is also a chemical resistance option, and multiple wiring options.



### Features and Benefits

- Point-to-point replacement of high performance TL-D waterproof luminaires up to 2.58W
- Energy savings up to 50%, dimmable (DALI) for even more savings
- Significant lower maintenance cost due to high system lifetime
- Chemical resistance and impact resistance combined in one product optionally
- Multiple Beam angles, lengths, and wiring connections
- Easy installation



Model	W (mm)	H (mm)	L (mm)
2ft	96	96	721
4ft	96	96	1342
5ft	96	96	1642

Dimensions in mm (Nominal)

### PACIFIC LED WATERPROOF BATTEN

Family Name	Pacific LED G3	Installation	Surface Mounted
Model	WT460C - Standalone Version WT461C - Chemical Resistance Version	IP rating	IP66
Lumen/ Watt	6400lm/ 54W 4200lm/ 35W 3500lm/ 28W 2300lm/ 22W	IK Rating	IK08
CCT	4000K	Weight	1500mm - 3.9kg 1200mm - 3.4kg 600mm - 1.7kg
Colour Rendering Index (CRI)	80	Colour of housing	Clear with light grey
Flex and Plug	No	Application	Industry, F&B, Parking, Semi Outdoor, Under Canopy, Underground
Lifetime L70*	50,000hrs	Accessories	Flexible ceiling bracket, Suspension Hooks, Ceiling clips, Cable glands, End cap 3 or 5 pole connector, Polycarbonate tube
Unified Glare Ratio (UGR)	22	Suspension Height - min/max	NA
Optics	NB, WB, VWB	Maximum Run Length	NA
Driver	Philips Xitanium Driver		
Dimmable	PSD (DALI), PSU (Fixed)		

\* = When the fitting reaches 70% of full potential (new)